



VPL 305·20 POI

Video Pixel Linear



Description

The VPL is a linear pixel product capable of reproducing powerful pixel mapping and media effects. It is a versatile tool for installations where high-visibility and excellent durability are essential. This easily integrated fixture is suitable for a wide range of applications, including media façades, stadiums, theme parks in exterior or interior environments. The VPL series are available in different lengths with multiple accessories like lenses, brackets, and extension cables.

Features and benefits

- ✓ IP66-rated Video Pixel Linear luminaire
- ✓ Power and data in one cable with no need for external power supplies
- ✓ 298 millimeter length per luminaire with integrated power supply
- ✓ Automatic or individual addressing
- ✓ 16 Quad Full-Color LED Pixel Clusters (64 Full-Color LEDs per unit)
- ✓ Long runs on a single circuit
- ✓ 19.05 mm pixel pitch and 120° viewing angle
- ✓ IK09-rated, UV and C5 corrosion resistant
- ✓ 16-bit control, Real time remote monitoring

Certifications & classifications

IP66
INGRESS


RoHS
COMPLIANT

CE


ETL
US

C5
CORROSION




VPL305-20, POI, AG



VPL610-20, POI, AG



VPL1220-20, POI, AG



Specification

Optical Data	LED expected lifetime (L70)	50,000 hours
	Lens options (built-in)	110°
	Lightsource	64 x high-power RGB LEDs
	Pixel per meter	52 px/m
	Pixel pitch	19.05 mm
	Pixel size	6 x 6 mm Quad LED Pixel Clusters
Photometric	Color temperature range	2000K - 10000K
	Efficacy	26 lm/W*
	Light output - all LEDs on	201 lm
	Lumen per kilogram	503 lm / Kg
	Luminance	2100 Nits (cd/m2) 2100 nits (modular spacing 35mm)
	Native beam angle(s)	109° (with clear 110° lens)
	Native field angle(s)	151° horizontal, 158° vertical (with 110° clear lens)
Physical	Color options	AluGrey
	Corrosion class	C5 (ISO 12944:2018)
	Effective Projected Area	0.16 Square ft
	IK rating	IK09
	IP class	IP66
	Material	Aluminium
	Net dimensions L x H x W (imperial)	11.7 x 2 x 1.5 inches
	Net dimensions L x H x W (metric)	298 x 52 x 38 mm
	Net weight	0.4 kg (0.9 lbs)
	Vibration Rating	3G
Features	Addressable pixels	16
	Auto addressing	Yes
	Color calibration	SGM proprietary, full color calibration White calibration for RGB
	Dimming	Smooth fade in, gamma corrected curve
	On-fixture test	Yes
	Other	LED frequency control via SGM Network Admin
	Remote monitoring	Yes (Real Time via RDM)
	View angle	120°

Electrical	Electrical protection	Overload protection with automatic recover
	Input voltage (nominal)	200 - 240 VAC; 50 / 60 Hz
	Max inrush current 230VAC	1.9 A
	Max power consumption	9 W
	Power factor	0.98 PF (230 V)
	Power per meter	29 W/m
	Power Supply Unit	Auto-ranging electronic switch-mode
	Standby power consumption	2.8 W
Programming and Control	16-bit control	Red, Green, Blue
	Data communication	100 Mb
	Data distribution	SGM Power and Data Joiner
	DMX channels	1, 3, 6, 12, 24, 48 or 96
	DMX modes	8
	Protocol	Art-Net (up to 120 Hz) sACN SGM VP-Net
	Setting and addressing	SGM Network Administrator
Connections	Data / Power input	Multicore 8 pin cable 1xShield, 2xPower, 4xSignal
	Data / Power output	Multicore 8 pin cable 1xShield, 2xPower, 4xSignal
	Power cable diameter	11mm ±0,3mm
Installation	Orientation	Any
	Rigging possibilities	Hanging / horizontal mounted or ceiling / wall mount (optional)
Thermal	Cooling	Passive
	Humidity (max.)	98 %
	Temperature range, operating	-20°C to 60°C
	Temperature range, start-up	-20°C to 60°C
	Temperature range, storage	-40°C to 80°C
	Thermal protection	Automatic overtemperature protection
	Total heat dissipation, max power	30.7 BTU per hour
	Total heat dissipation, standby	9.6 BTU per hour
Included items	Included items	Safety instructions and installation quick guide
Conforms To	CE - 2014/30/EU: EMC Directive	EN 55015

		EN 61547 EN 61000-3-2 EN 61000-3-3 EN 55032 EN 55035
	CE - 2014/35/EU: Low Voltage Directive	EN 60598-1 EN 60598-2-17 EN 62471 EN 60529 EN 62368-1
	RoHS2 Directive	2011/65/EU
	UL	UL Std. 1573
Certified To	CSA	CSA-E598-2-17-98, Ed: 1 CSA E60598-1, Ed: 3

Ordering information

Qty	Product name	Item number
☐	VPL305-20, POI, AG	80080052
☐		
	Accessories	Item number
☐	VPL Rounded Opal lens	83061074
☐	VP Power Inserter	83062047
☐	VP Touring Power + Data Joiner	83062049
☐	VP Data Redundancy Interface	83062048
☐	VPL Single installation bracket	83060634
☐	VPL Dual installation bracket	83060635
☐	VP Extension cable	83062051
☐	VP Connector End cap	83062056
☐	SGM Network Admin	
☐	VP Power + Data Joiner	83062046
☐	VPL Smoked clear lens	83061079
☐	GND/Earth wire for VPL, 1m	83062050
☐	VPL Opal / Black lens	83061083
☐	VPL Smoked Frosted lens	83061087
☐	VPL Rounded Smoked Opal lens	83061091
☐	VP Extension cable, 1m	83062051
☐	VP Extension cable, 2.5m	83062052
☐	VP Extension cable, 5m	83062053
☐	VP Custom Extension cable Kit, 1m	83062054
☐	VP Custom Extension cable Kit, 10m	83062055
☐	VPL Dual Wing Installation Bracket	83060720
☐	PDM - Power & Data Manager	80070240
☐		



Headquarters [+45 70 20 74 00](tel:+4570207400)

Mail info@sgmlighting.com

Website sgmlighting.com