


Photometric Report




Manufacturer	SGM
Luminaire	Palco 6 RGBL 10deg CTC at 75 Peak Preliminary
Measurement Date	29/08/2025
Power Consumption	676.0 W
Light Output	30 520 lm
Field Angle H.	23.9 deg
Beam Angle H.	11.9 deg
Field Angle V.	23.9 deg
Beam Angle V.	11.9 deg
Center Beam Intensity	458 152 cd
Color Temperature	3 226 K
CRI	84
CQS	86
TLCI	72
TM30 Rf/Rg	82/112
PPF	442.71 $\mu\text{mol/s}$



Lux Diagram




Polar Distribution




□ Horizontal 0°H



Beam Profile



Spectral Distribution




Photometric Report




Local Average Values

Hue Bin	Rf	Chroma	Hue
1	85	5%	-5%
2	93	1%	-1%
3	83	2%	8%
4	78	6%	13%
5	80	13%	10%
6	76	16%	2%
7	75	14%	-8%
8	81	3%	-12%
9	87	-2%	-9%
10	85	-8%	2%
11	76	-5%	15%
12	78	4%	15%
13	82	9%	11%
14	79	14%	12%
15	81	12%	0%
16	82	14%	-6%

Color Vector Graphics




Global Average Values (TM-30)



TLCI-2012: 72

Sector	Lightness	Chroma	Hue
Red	-1	0	0
Red/Yellow	0	0	-2
Yellow	0	-2	-2
Yellow/Green	0	-3	0
Green	-1	-3	0
Green/Cyan	1	-2	6
Cyan	1	0	3
Cyan/Blue	2	1	0
Blue	0	-3	-3
Blue/Magenta	1	-2	1
Magenta	0	-3	2
Magenta/Red	-1	-2	2

CRI: 84



Color Quality Scale (CQS): 86

